




HR LABORATORY REFRIGERATOR SOLID DOOR

NULINE
REFRIGERATION

FEATURES

- Fan Forced System
- Door Lock
- Data Logger Included
- Digital Display with Built-in Alarms
- Hi/Lo Readout
- Remote Alarm Contacts
- Door Fan Switch
- ARTG Number 269856



	2°C to 8°C
	135 L 350 L 570 L
	595w x 650d x 830h 595w x 650d x 1850h 775w x 750d x 1850h



HR LABORATORY REFRIGERATOR SOLID DOOR

NULINE
REFRIGERATION

Model	HR200P	HR400P	HR600P
Gross Capacity	135 L	350 L	570 L
External Dimensions in mm (w/d/h including castors)	595 x 650 x 830	595 x 650 x 1850	775 x 750 x 1850
Internal Dimensions in mm (w/d/h)	455 x 445 x 665	455 x 445 x 1685	635 x 545 x 1685
Packed Dimensions in mm (w/d/h including pallet)	640 x 670 x 1005	640 x 670 x 2010	830 x 790 x 2010
Gross Weight - kg (packed weight)	48	85	102
Net Weight - kg	45	77	95
Energy Consumption	237 kWh/y	330 kWh/y	491 kWh/y
Voltage	240V		
Temperature Range	2°C to 8°C		
Ambient Temperature Range	10°C to 32°C		
Refrigerant	R600a	R290	
Cooling System / Defrost	Fan Forced / Automatic		
Exterior Cabinet Finish	Enamelled Steel		
Inner Liner Material	ABS		
Door	Solid		
Door Hinge	RH (LH upon request)		
Door Handle	Pull Handle		
Type of Controller	Digital		
Temperature Display	External		
Data Logger	Included		
Door Ajar Alarms	Optional	Standard	
High and Low Readout	Visual / Audible		
BMS Connectivity (BMS Connectivity for Remote Alarms only)	Yes		
(BMS Connectivity for 4-20mA Transmitter)	Optional		
Port Entry	Optional	Standard	
Battery Back-up for Controller	Optional	Standard	
Power Requirement	10amp GPO		
Watts	81W	178W	160W
Castors	Levelling Legs		
Adjustable Shelves	4	10	
Usable Shelf Area in mm(w/d)	3 x 530 x 652 1 x 438 x 202	9 x 455 x 405 1 x 438 x 202	9 x 635 x 505 1 x 618 x 302
Light	LED	N/A	

Nuline Refrigeration reserves the right to alter the specifications without prior notice.