




MLi REFRIGERATOR INCUBATOR

NULINE
REFRIGERATION

FEATURES

- Fan Forced System
- Voltage Free Connection
- Door Lock
- Door Ajar Alarms
- Interior LED Lighting
- Automatic Condensate Water Disposal
- Digital Display with Built-in Alarms
- Hi/Lo Readout



	2°C to 40°C
	29 L 59 L 125 L
	445w x 458d x 535h 450w x 460d x 875h 595w x 610d x 840h



MLi REFRIGERATOR INCUBATOR



Model	MLi29GP	MLi59GP	MLi125GP/P
Gross Capacity	29	59 L	125 L
External Dimensions in mm (w/d/h including castors)	445 x 458 x 535	450 x 460 x 875	595 x 610 x 840
Internal Dimensions in mm (w/d/h)	361 x 205 x 400	390 x 300 x 720	505 x 442 x 625
Packed Dimensions in mm (w/d/h including pallet)	500 x 575 x 590	525 x 560 x 900	660 x 705 x 910
Gross Weight - kg (packed weight)	30	41	59
Net Weight - kg	27	38	55
Voltage	220V		240V
Temperature Range	2°C to 40°C		
Ambient Temperature Range	10°C to 32°C		
Temperature Fluctuation	±1°C		
Refrigerant	R600a		
Cooling System / Defrost	Fan Forced / Automatic		
Exterior Cabinet Finish	White Enamel		
Inner Liner Material	ABS		
Door	Glass	Glass	Glass
Door Hinge	RH		
Door Handle	Pull Handle		
Type of Controller	Digital		
Temperature Display	External		
Data Logger	Optional		
Door Ajar Alarms	Yes		
High and Low Readout	Visual / Audible		
BMS Connectivity			
(BMS Connectivity for Remote Alarms only)	Yes		
(BMS Connectivity for 4-20mA Transmitter)	Optional		
Port Entry	Yes		
Battery Back-up for Controller	N/A		
Power Requirement	10amp GPO		
Castors	Adjustable Levelling Legs		
Adjustable Shelves	2	3	4
Usable Shelf Area in mm(w/d)	2 x 376 x 190	2 x 368 x 287 1 x 378 x 190	2 x 488 x 411 2 x 488 x 276
Light	LED		
Noise	45 dB(A)		

Nuline Refrigeration reserves the right to alter the specifications without prior notice.