

# ML SERIES VACCINE REFRIGERATOR

**NULINE**  
REFRIGERATION

## FEATURES

- Fan Forced System
- Voltage Free Connection
- Door Lock
- Door Ajar Alarms
- Interior LED Lighting
- Automatic Condensate Water Disposal
- Fan Door Switch
- Data Logger Included
- Battery Backup for Controller
- Digital Display with Built in Alarms
- Hi / Lo Read Out
- Self Closing Door
- ARTG Number 269893



2°C to 8°C



29 L  
59 L  
125 L  
300 L  
500 L



445w x 500d x 550h  
450w x 460d x 875h  
595w x 610d x 840h  
595w x 611d x 1560h  
700w x 660d x 2020h

+61 3 9562 3355

info@nuline.au

[www.nuline.au](http://www.nuline.au)

+64 9 884 4181

info@nuline.co.nz

[www.nuline.co.nz](http://www.nuline.co.nz)



# ML SERIES VACCINE REFRIGERATOR



Model	ML29GP	ML59GP	ML125GP/P
Gross Capacity	29 L	59 L	125 L
External Dimensions in mm (w/d/h including castors)	445 x 500 x 550	450 x 460 x 875	595 x 610 x 840
Internal Dimensions in mm (w/d/h)	361 x 205 x 400	390 x 300 x 720	505 x 442 x 625
Packed Dimensions in mm (w/d/h including pallet)	500 x 576 x 590	525 x 560 x 900	660 x 705 x 910
Gross Weight - kg (packed weight)	32	41	59
Net Weight - kg	27	38	55
Voltage	220V		
Temperature Range	2°C to 8°C		
Ambient Temperature Range	10°C to 32°C		
Refrigerant	R600a		
Cooling System / Defrost	Fan Forced / Automatic		
Exterior Cabinet Finish	Enamelled Steel		
Inner Liner Material	ABS		
Door	Glass	Glass	Glass / Solid
Door Hinge	RH		
Door Handle	Pull Handle		
Type of Controller	Digital		
Temperature Display	External		
Data Logger	Standard		
Door Ajar Alarms	Standard		
High and Low Readout	Visual / Audible		
BMS Connectivity			
(BMS Connectivity for Remote Alarms only)	Standard		
(BMS Connectivity for 4-20mA Transmitter)	Optional		
Port Entry	Standard		
Battery Back-up for Controller	Standard		
Power Requirement	10amp GPO		
Castors	Adjustable Levelling Legs		
Adjustable Shelves	2	3	4
Usable Shelf Area in mm(w/d)	2 x 376 x 190	2 x 368 x 287 1 x 378 x 190	2 x 488 x 411 2 x 488 x 276
Light	LED		

Nuline Refrigeration reserves the right to alter the specifications without prior notice.

# ML SERIES VACCINE REFRIGERATOR



Model	ML300P	ML500P
Gross Capacity	300 L	500 L
External Dimensions in mm (w/d/h including castors)	595 x 611 x 1560	700 x 660 x 2020
Internal Dimensions in mm (w/d/h)	505 x 442 x 1345	610 x 477 x 1735
Packed Dimensions in mm (w/d/h including pallet)	660 x 705 x 1630	760 x 735 x 2100
Gross Weight - kg (packed weight)	77	132
Net Weight - kg	73	122
Voltage	220V	
Temperature Range	2°C to 8°C	
Ambient Temperature Range	10°C to 32°C	
Refrigerant	R600a	
Cooling System / Defrost	Fan Forced / Automatic	
Exterior Cabinet Finish	Enamelled Steel	
Inner Liner Material	ABS	
Door	Solid	
Door Hinge	RH	
Door Handle	Pull Handle	
Type of Controller	Digital	
Temperature Display	External	
Data Logger	Included	
Door Ajar Alarms	Yes	
High and Low Readout	Visual / Audible	
BMS Connectivity		
(BMS Connectivity for Remote Alarms only)	Yes	
(BMS Connectivity for 4-20mA Transmitter)	Optional	
Port Entry	Yes	
Battery Back-up for Controller	Yes	
Power Requirement	10amp GPO	
Castors	Adjustable Levelling Legs	Yes
Adjustable Shelves	7	
Usable Shelf Area in mm(w/d)	6 x 488 x 411 1 x 488 x 276	6 x 593 x 470 1 x 593 x 300
Light	LED	



Nuline Refrigeration reserves the right to alter the specifications without prior notice.