Economy Refrigerated Incubator (0°C~+65°C)

Features:

- LCD Display.
- Polished stainless steel chamber.
- Round angle structure easy to clean.
- Universal casters for easy movement.
- CFC-free eco-friendly refrigerant.
- Microprocessor PID temperature control acurate and reliable.
- Power socket integrated inside for additional small equipment.

Safety Function:

- Temperature protection threshold value can be set.
- Auto-off protection and alarm for abnormal situation.
- Parameters can be saved automatically when power off or system error.



| Model | ICBOD-80-B | ICBOD-150-B | ICBOD-200-B | ICBOD-250-B | ICBOD-300-B | ICBOD-400-B |
|-------------------|--------------------------------|--------------|--------------|--------------|--------------|--------------|
| Capacity | 80L | 150L | 200L | 250L | 300L | 400L |
| Temp. Range | 0~65°C | | | | | |
| Temp. Fluctuation | ±1°C (heating: +/-0.5°C) | | | | | |
| Temp. Uniformity | ±2°C | | | | | |
| Time Range | 0~999min | | | | | |
| Shelves | 2 - adjustable 3 - adjustable | | | | | |
| Refrigerant | R134a (CFC free, eco-friendly) | | | | | |
| StandardAccessory | BOD socket | | | | | |
| Consumption | 180W | 250W | 300W | 300W | 400W | 550W |
| Power Supply | AC240V, 50Hz, 10Amp | | | | | |
| Internal Size(mm) | 400*370*550 | 450*420*850 | 450*450*1000 | 480*490*1070 | 520*500*1170 | 580*540*1270 |
| External Size(mm) | 540*570*1070 | 590*620*1370 | 590*640*1520 | 620*680*1590 | 660*690*1690 | 720*740*1790 |
| Gross Weight(kg) | 85 | 120 | 138 | 147 | 157 | 170 |



Laboratory Equipment Pty Ltd email: sales@labec.com.au Ph: 02 9560 2811 • Fax: 02 9560 6131 www.labec.com.au